

Commercial Doors



www.mmidoor.com





2419331031409 30.00



ABOUT MMI DOOR

For over 60 years, MMI DOOR has earned the reputation of being the preferred door supplier to home centers and building supply dealers. With 3 locations servicing all or portions of the 48 continental United States; MMI DOOR is a true, single source door provider. Our product lines are available through most major building supply dealers and home centers nationwide. Throughout the decades, we've expanded our door product offering significantly and confidently maintain our position as an industry leader.

Superior products deserve superior service. That is where MMI DOOR employees excel. Customer focused and dedicated to doing it right the first time; MMI DOOR employees are responsive, reliable and informed. It is our people that make the difference.

Our industry continues to evolve and so does MMI DOOR. One of our primary goals is to keep our customers strong in a changing environment. We strive to be the most dependable and innovative, value-add fabricator in the marketplace.



Our products are stored, assembled and staged in over 700,000 square feet of heated warehouses. Strict quality control standards are followed, allowing us to deliver maximum value. With one of the largest and most diverse inventories in the country, MMI DOOR offers product opportunities that are second to none.

Commercial Solutions

MMI DOOR offers numerous services to satisfy your commercial project needs, such as:

- On site consulting
- Door and hardware schedule coordination
- Keying services
- Door and frame fabrication (welding, preps and reinforcements)
- Commercial hardware application
- In-house prefinishing in 25 stock colors

Taking our services a step further, we have also implemented a process that makes ordering with MMI DOOR easy, efficient, and profitable.

Our process goes as follows:

1. Evaluation Stage

An extensive meeting with decision makers from both sides to determine your total needs as it relates to our commercial products and services.

2. Preparation Stage

MMI DOOR Management works directly with the appropriate supply chain members to meet all needs - new, unique or unconventional.

3. Presentation Stage

MMI DOOR returns with the appropriate parties to present the final solutions. The objective is to address all open issues and deliver your ultimate program.

4. Coordination Stage

Once the commitment is obtained, MMI DOOR takes control of the supply chain by:

- Documenting roles of all players Manufacturers, MMI Door, Dealers and the Builders
- Ensuring that each understands his role and is ready to execute
- · Assigning accountable parties at all levels

5. Execution Stage

This is our time and we take it very seriously. We are your single source solution point.

> **MMI DOOR Takes Ownership** of the Supply Chain.

We Make It Easy, Efficient and Profitable!







Commercial Solutions

Ordering Process

Sourcing commercial products can be complicated, time consuming and frustrating. Our program is designed to simplify that process.

It is driven by:

- Simplicity We make it easy for you and your customer.
- Speed Commercial products delivered at residential speeds.
- Convenience One stop shop concept; residential and commercial products from one source.


Today, value added services are required to minimizing errors and lowering jobsite costs. Our program provides unique services to lower your costs and improve the overall process. Such as:

- Prehanging Many light commercial and fire doors can actually be prehung.
- **Prefinishing** We provide residential, commercial doors and frames painted in 25 popular colors.
- **Pre-applied Hardware** Closers, exit devices, locksets we apply, saving valuable jobsite labor, errors or damage.


Imagine a commercial job prehung, prefinished and with all the hardware applied!

We make the ordering process simple!















Exterior Paint Options 25 Prefinished Options

Paint Selections

MMI DOOR BOLD Colors



Standard Colors






Commercial Door Frames

Residential or Light Commercial Application

Residential and Light Commercial Frames **EZFLEX**



Universal Application

(Adjustable Split Frame - Interior & Exterior Application)

Main frames are 18 gauge and closure trim is 22 gauge for walls up to 7-1/2" walls over 7-1/2" is 18 gauge.

* Stock sizes may vary between distribution centers





Our EZ Flex Steel door frame is an adjustable steel frame with a kerf for weatherstripping, designed for prehanging applications for residential or light commercial, new or remodeling construction. The EZ Flex Steel Frame is also a solution for 90 minute applications from house to garage, as well as light commercial and multi-family projects where prehung door units save time and money on installation. Other specs include:

- NAMI 90 MIN neutral and positive pressure fire rated label, wood or steel studs
- · Constructed of 18 gauge galvannealed A60 steel
- · Can be prehung with adjustable or ADA compliant sill
- 3 adjustable frame sizes available*:

[4-1/2"-5-1/2"] [5-1/2"-6-1/2"] [6-1/2"-7-1/2"] (1" adjustments, special/custom sizes are available*)

- 1-3/4" doors only
- 5/8" stop height
- · Removal without damage to the existing wall
- · Includes anchoring holes and nail clearance slots for wood casing
- · Hinge prep for 4"
- 2-3/4" deadbolt prep and 2-3/4" adjustable T-strike prep
- · Prefinished white or field paintable
- Compatible with masonry wood, or steel stud for easy installation
- Standard threshold prep

Options

- · Special hinge or strike locations
- 4-7/8" ASA strike prep
- 2-1/4" Full lip strike prep
- · Aluminum or Steel Casing
- · Option on low profile (ADA Compliant Sill)





18 Gauge Steel Fixed Frame

Our EZ Steel Frame is a fixed throat, prefinished, standard door frame designed for interior applications in new construction and light commercial projects such as assisted living, hotel/motel, office and residential. Other specs include:

- NAMI 90 MIN neutral and positive pressure fire rated label, wood or steel studs
- · Constructed of 18 gauge galvannealed A60 steel
- 2 Fixed frame sizes available*:

4-5/8" 4-7/8"

(10 other sizes varying from 4" to 7-3/8" are available as well as special/custom sizes*)

- Available for both 1-3/8" and 1-3/4" doors
- 5/8" stop height
- · Removable without damage to existing wall
- Hinge preps: 4" and 4-1/2"**
- 2-3/4" adjustable T-strike prep
- Prefinished steel casing to match frame (1-1/2" width)
- · Prefinished brown or field paintable
- Knock down ready to install

Options

- · Special hinge or strike locations
- Non-standard wall size
- 4-7/8" ASA strike prep
- 2-1/4" Full lip strike prep
- 2-3/4" Deadbolt prep
- Kerf fixed throat frame option
- Standard threshold prep
- Prefinished aluminum casing to match frame (1-1/2" width)
- Prefinished colonial casing to match frame (1-3/4" width)

RATING 20 MIN 20 Minute Fire Rated Doors

Light Commercial Doors

Residential style with commercial grade safety for your home. Sized and prepped for wood, EZ FLEX & EZ Steel Frames.

- Applications: Apartments, hotels/motels, assisted living facilities, safe rooms, home offices, storage/furnace rooms, house to garage doors.
- 25 Paint Colors Available (Steel & Fiberglass Doors Only)
- Frame Options: In-stock

20 MIN Fire Rated Wood Frames

Steel & Fiberglass 20 Minute Fire Doors



MJ 21 Majestic Steel 6 Panel 2/6 x 6/8 2/8 x 6/8 2/10 x 6/8 3/0 x 6/8 3/6 x 6/8



MJ CR 1 Majestic Steel 1 Panel 2/6 x 6/8 2/8 x 6/8 2/10 x 6/8 3/0 x 6/8 3/6 x 6/8



MJ CR 2 Majestic Steel 2 Panel 2/8 x 6/8 2/10 x 6/8 3/0 x 6/8



MJ CR 3 Majestic Steel 3 Panel 2/8 x 6/8 2/10 x 6/8 3/0 x 6/8



FS 20 Fiberglass Smooth 2 Panel 2/8 x 6/8 3/0 x 6/8



FS 21 Fiberglass Smooth 6 Panel 2/8 x 6/8 3/0 x 6/8



FS 22 Fiberglass Smooth 2 Panel 2/8 x 6/8 3/0 x 6/8



FS 200 Fiberglass Smooth 2 Panel Planked 2/8 x 6/8 3/0 x 6/8



FS 30 Fiberglass Smooth 3 Panel Craftsman 2/8 x 6/8 3/0 x 6/8

Molded Fire Door Units 20MIN

- · Available complete with Fire Rated frame
- · Solid core
- Machining option
- 20 Minute NAMI Fire Label applied to door panel
- 60 Minute molded rated doors available in raised panel styles



2 Panel Smooth Surface Ovolo Sticking 2/8 x 6/8 3/0 x 6/8



2 Panel Arch Smooth Surface Ovolo Sticking 2/8 x 6/8 3/0 x 6/8



3 Flat Panel Smooth Surface Craftsman Sticking 2/8 x 6/8 3/0 x 6/8



5 Panel Smooth Surface Cove & Bead Sticking 2/8 x 6/8 3/0 x 6/8




2 Panel Planked Arch Smooth Surface Ovolo Sticking 2/8 x 6/8 3/0 x 6/8



Commercial Door Frames

Heavy Commercial Application





Anchor

Wood Stud

Anchor

Metal Stud Anchor

Multipurpose

Anchor

Commercial Frames Hollow Metal 5-3/4" (SU)* Frame Includes:


- 16 gauge galvanized primed gray
- · Reinforced for closer
- Prepped and reinforced for 3 4-1/2" square corner hinges and 4-7/8" strike prep

2" Head


frame face


dimension


- Fire rated NAMI embossed fire labels
- · Assembled, welded or knock down
- · Handed for left or right swing (inswing or outswing)
- · Anchors (must specify)
- 3 rubber mutes
- Will work with block walls, poured walls, metal studs or wood studs for new construction and/or existing construction (Other sizes and profiles available special order)
- * (SU) Universal Frame Interior and exterior application




Universal **Application** (Interior & Exterior Application)










Hollow Metal (DU)** Frame Includes:

- 16 gauge cold rolled primed gray
- Reinforced for closer (optional)
- Prepped and reinforced for 3 4-1/2" square corner hinges and 4-7/8" strike prep
- · Fire rated NAMI embossed fire labels
- · Integral adjustable plumb anchor
- · 4 tab interlocking system
- · Knock down, ready to install
- · Handed for left or right swing
- 3 rubber mutes (Other sizes and profiles available special order)
- ** (DU) Drywall Frame -Interior application only



16 Gauge Adjustable Steel Frames


4-7/8"

Throat


-5 - 3/4

Frame depth


- · A40 paintable galvanneal steel un-primed
- 3 4-1/2" high frequency hinge reinforcements
- ASA (4-7/8") strike prep
- Bumper/silencer holes (3 at strike jambs and 2 at double heads)
- All double heads undersized by 1/8" from nominal width
- Mechanical K.D. corner connection
- · Faces punched and dimpled for wall anchoring
- NAMI label embossment standard on 6'8" and 7'0" hinge jambs (up to 1-1/2 hr)
- Jamb depths adjustable from 5-1/2" to 8-3/4", 8-1/2" to 13-1/4"







Adjustable Application (Interior & Exterior Application)



8-1/2" to 13-1/4 Jamb Depth

Commercial Doors

Heavy Commercial Application

Commercial Doors

- Applications: Office buildings, hotels, motels and assisted living facilities
- 25 Paint Colors Available (Steel Doors Only)
- · Frame Options: In-stock Fire Rated 16 gauge hollow metal steel frames - galvanized or cold rolled
- · Door Options: In-stock



Red Oak Wood Door

2/8 x 6/8 3/0 x 6/8 3/0 x 7/0



White Birch Wood Door

2/8 x 6/8 3/0 x 6/8 3/0 x 7/0

- 20 MIN Fire label (also available non-rated)
- Partical core
- Prep for 161 lock prep
- Prepped for 3 4-1/2" square corner hinges
- · Handed for left or right swing



Red Oak Wood Door 3/0 x 6/8

3/0 x 7/0

- 90 MIN Fire label
- Mineral core
- Prepped for 161 lock prep
- Prepped for 3 4-1/2" square corner hinges
- · Handed for left or right swing
- Hardware Options: In-stock (see page 15 & 16)

 - Commercial grade locks Self closing hinges

White Birch

Wood Door

2/8 x 6/8

3/0 x 6/8

3/0 x 7/0

- Door closers
- Door holders and stops
- Exit devices
- Lites and louvers
- Other Options: In-stock
 - · Hardware applied






6 Panel Steel Door 2/8, 2/10 & 3/0 x 6/8 2/8, 2/10 & 3/0 x 7/0



Flush Steel Door 2/6, 2/8, 3/0, 3/6 & 4/0 x 6/8 2/6, 2/8, 3/0, 3/6 & 4/0 x 7/0

- · Non-rated and fire rated NAMI embossed fire labels
- 18 Gauge galvanized polystyrene core primed gray
- · Reinforced for closer
- Reinforced for hinges
- Prepped for 3 4-1/2" square corner hinges
- Available with 161 lock prep on stock 3/0 flush doors
- 86 edge prep only available on special order for other products
- Closed top channel



Commercial Door Options

90 Minute Fire Rated Doors RATING 90 MIN



90 Minute Fire Doors

Must purchase 1 package of Thru Bolts (SN134) to apply door closer because of mineral core in wood door.

*Special Order Only



Red Oak Wood Flush 3/0 x 6/8 3/0 x7/0



White Birch Wood Flush 2/8 x 6/8 3/0 x 6/8 3/0 x7/0



MJ1 Majestic Steel 24 Gauge Flush 2/6 x 6/8 2/8 x 6/8 2/10 x 6/8 3/0 x 6/8 3/6 x 6/8



MJ 21 Majestic Steel 24 Gauge 6 Panel 2/6 x 6/8 2/8 x 6/8 2/10 x 6/8 3/0 x 6/8 3/6 x 6/8



MJ 120 Majestic Steel 24 Gauge 8 Panel 2/8 x 6/8 3/0 x 6/8



MJ CR10* Majestic Steel 24 Gauge 1 Panel 2/8 x 6/8 2/10 x 6/8 3/0 x 6/8



MJ CR20* Majestic Steel 24 Gauge 2 Panel 2/8 x 6/8 2/10 x 6/8 3/0 x 6/8



MJ CR30* Majestic Steel 24 Gauge 3 Panel 2/8 x 6/8 2/10 x 6/8 3/0 x 6/8



MJ 22 Majestic Steel 24 Gauge 2 Panel Arch 2/8 x 6/8 3/0 x 6/8



MJ 20 Majestic Steel 24 Gauge True 2 Panel 2/8 x 6/8 3/0 x 6/8




MJ 40 Majestic Steel 24 Gauge 4 Panel 2/8 x 6/8 3/0 x 6/8

Light Commercial Doors

Residential styling, commercial grade safety for your home. Sized and prepped for wood, EZ FLEX & EZ Steel Frames.

- Applications: Apartments, hotels/motels, assisted living facilities, safe rooms, home offices, storage/ furnace rooms, house to garage doors.
- Frame Options: In-stock 90 MIN Fire rated 18 gauge adjustable Steel Frame







90 Minute Fire Doors Reinforced for Hardware

** Reinforcements for closers & exit devices (Suited for hardware applications)



MJ 1R** Majestic Steel 24 Gauge Flush 2/8 x 6/8 3/0 x 6/8



MJ 21R** Majestic Steel 24 Gauge 6 Panel 2/8 x 6/8 3/0 x 6/8 3/6 x 6/8

Commercial Door Options

Lites & Louvers

Lites & Louvers

MMI DOOR carries a selection of lites and louvers to address most common applications. Our non-rated lites contain clear glass and our fire rated lites have wire glass. Prior to selection, simply determine as to whether or not a fire rating is required. Then choose the shape, size and positioning of the lite or louver you desire. Our Customer Service Representatives can help you through this process.



V 10" x 10" Lite Available in Non Rated and Fire Rated Glass



3" x 33" Lite 4" x 25" Lite 5" x 20" Lite Available in Non Rated and Fire Rated Glass

NL5



G 22" x 28" (6'8") Lite 22", 24" x 30" (7'0") Lite Available in Non Rated and Fire Rated Glass



LVR 24" x 12" Lite Metal Louver Not Fire Rated







Commercial Hardware - Interior & Exterior Application

MMI DOOR stocks a full line of commercial doors, frames and hardware available for immediate delivery. Many of these items are adaptable to our residential products in this catalog. We offer a variety of commercial hardware such as self closing hinges, automatic door closers, panic devices and more to suit most applications.



Fiberglass Flush Glazed ADA Compliance - Special Order Only



Commercial Doors Handings & Sizes

Commercial Door Handings (Viewed from Keyed Side of Door)

INSWING









Left Hand Active

Right Hand Active

OUTSWING









Left Hand Reverse

Right Hand Reverse

Left Hand Reverse Active


Right Hand Reverse Active

Opening Sizes for Steel Frames Slip-on Drywall Application


Drywall Frame



Expo	anda	ble F	rame







	Rough Opening				
Door Size	Width	Height			
2/6 x 6/8	32"	81"			
2/8 x 6/8	34"	81"			
3/0 x 6/8	38"	81"			
3/6 x 6/8	44"	81"			
4/0 x 6/8	50"	81"			
6/0 x 6/8	74"	81"			
3/0 x 7/0	38"	85"			
3/6 x 7/0	44"	85"			
4/0 x 7/0	50"	85"			
6/0 x 7/0	74"	85"			

Head and side frame face dimension 2"	1
---------------------------------------	---

	Rough Opening				
Door Size	Width	Height			
3/0 x 6/8	37-5/8"	80-13/16"			
6/0 x 6/8	73-5/8"	80-13/16"			
3/0 x 7/0	37-5/8"	84-13/16"			
6/0 x 7/0	73-5/8"	84-13/16"			

Rough Opening				
Door Size	Width	Height		
2/8 x 6/8	33-1/4"	81"		
3/0 x 6/8	37-1/4"	81"		
6/0 x 6/8	73-1/4"	81"		
3/0 x 7/0	37-1/4"	85"		
6/0 x 7/0	73-1/4"	85"		

Universal Frame

Butted Application



	Head Frame Rough Ope		Opening	ning Unit Dimension	
Door Size	Face Dimension	Width	Height	Width	Height
2/6 x 6/8	2"	34-1/4"	82-1/8"	34"	82"
2/8 x 6/8	2"	36-1/4"	82-1/8"	36"	82"
2/10 x 6/8	2"	38-1/4"	82-1/8"	38"	82"
3/0 x 6/8	2"	40-1/4"	82-1/8"	40"	82"
3/6 x 6/8	2"	46-1/4"	82-1/8"	46"	82"
4/0 x 6/8	2"	52-1/4"	82-1/8"	52"	82"
6/0 x 6/8	2"	76-1/4"	82-1/8"	76"	82"
2/6 x 7/0	2"	34-1/4"	86-1/8"	34"	86"
2/8 x 7/0	2"	36-1/4"	86-1/8"	36"	86"
2/10 x 7/0	2"	38-1/4"	86-1/8"	38"	86"
3/0 x 7/0	2"	40-1/4"	86-1/8"	40"	86"
3/0 x 7/0	4"	40-1/4"	88-1/8"	40"	88"
3/6 x 7/0	2"	46-1/4"	86-1/8"	46"	86"
4/0 x 7/0	2"	52-1/4"	86-1/8"	52"	86"
6/0 x 7/0	2"	76-1/4"	86-1/8"	76"	86"
6/0 x 7/0	4"	76-1/4"	88-1/8"	76"	88"

Custom head & face dimensions available upon request



Standard Application



Frame Opening		Rough Opening		Unit Dimension		
Door Size	Width	Height	Width	Height	Width	Height
2/6 x 6/8	30"	80-7/8"	31"	81-1/8"	33-5/8"	82-11/16"
2/8 x 6/8	32"	80-7/8"	33"	81-1/8"	35-5/8"	82-11/16"
2/10 x 6/8	34"	80-7/8"	35"	81-1/8"	37-5/8"	82-11/16"
3/0 x 6/8	36"	80-7/8"	37"	81-1/8"	39-5/8"	82-11/16"

ADA Application

	Frame	Frame Opening Rough Opening		Opening	Unit Dimension	
Door Size	Width	Height	Width	Height	Width	Height
2/6 x 6/8	30"	80"	31"	80-1/2"	33-5/8"	80-13/16"
2/8 x 6/8	32"	80"	33"	80-1/2"	35-5/8"	80-13/16"
2/10 x 6/8	34"	80"	35"	80-1/2"	37-5/8"	80-13/16"
3/0 x 6/8	36"	80"	37"	80-1/2"	39-5/8"	80-13/16"

Commercial Doors

Hardware Options



the Door



Ball Bearing Hinge 4-1/2" x 4-1/2" MPB79 26D MPB68 26D



NRP Ball Bearing Hinge 4-1/2" x 4-1/2" MPB68-NRP 26D MPB91-NRP 32D



Spring Hinge 4-1/2" x 4-1/2" MPS 60 26D


2 Secure the Door with Lock, Flush Bolts, Panic Bars, etc.



Augusta Design 626 Satin Chrome




Passage 4601LN Both levers always active.



4602LN Outside lever locked by inside push button. Inside lever always active. Unlocked by turning inside lever or emergency key in exterior.

Privacy



Entry


emergency key in exterior.

4607LN Outside lever locked by inside push button. Inside lever always active. Unlocked by turning inside lever or




Key in Lever or Passage Function **Exterior Trim** AU446F - Keyed AU448F - Passage


626 Satin Chrome



Classroom 4608LN Outside locked by key in outside lever. Inside lever always active.



Storeroom 4605LN Outside lever always locked. Inside lever always active.



Single Cylinder Deadbolt D212 (edge view) Outside locked by key in outside. Inside locked by turn latch.



Light Traffic Rim Panic Bar 1800 - Non Rated 1800F - Fire Rated 689 Aluminum Painted



Heavy Traffic Rim Panic Bar 2100-36 - Non Rated 2100F-36 - Fire Rated 630 Satin Stainless Steel



1810-36 Non Rated 1810F-36 Fire Rated 689 Aluminum Painted 630 Satin Stainless Steel

Heavy Traffic 2110 36-Non Rated 2110F-36-Fire Rated



* Dummv Lever AU4655LN



Lever with Escutcheon **Exterior Trim**

AU426F LHR - Left Hand Reverse AU426F RHR - Right Hand Reverse 626 Satin Chrome



Rim Cylinder 1109 626 Use with Escutcheon Trim



Thru Bolt SN-134 689 4 Pk



Dustproof Strike 570 US26D



Steel Door Flush Bolt 555 US26D

Commercial Doors

Hardware Options





Regular Arm Mount

Top Jamb Arm Mount





Parallel Arm Mount

Holder/Stop Arm Mount

Closer includes hardware pack for regular arm, top jamb arm mounting, parallel arm and holder/stop arm installation.

4 Protect the Door with Push & Pull Plates, Kick Plates, etc.

Includes Thru Bolts and Cover 689 Aluminum Painted




Seal the Door with Weatherstrip, Sweep and Threshold




Weatherstrip Adhesive Back 20 ft. roll S888BL20



Weatherstrip Perimeter Gasket $6/0 \times 7/0 \text{ set}$ 303AS





Barn Door Collection

Interior Doors that Elevate your Decor



Barn Door Collection

Hardware

Product Description:

- Hardware available to support 1-3/8" and 1-3/4" thick doors weighing up to 250 lbs.
- Kits available in 78-3/4" and 90" track lengths, including door straps, all mounting hardware and floor guide options
- · Available in three factory finishes ready to install: Matte Black, Stainless Steel and Oil Rubbed Bronze
- Ideal for openings 28" 34" wide for 78-3/4" track and openings 34"- 44" wide for 90" track
- Unique barn door style hardware enables the door to slide parallel to the wall
- Use for closets, room dividers or passage door applications
- Available accessories: Track joiner for bi-parting door application, door handle, and recessed door pull

Available Finishes:







Available Barn Door Kit Options:



Top of Door Mount Kit



Bent Strap Kit



Door Handle



Recessed Door Pull

In-Stock Barn Door Collection

7/0 Barn Doors







Primed K Bar Planked Door with Matte Black Top Mount Track and **Mounting Board**

K and Z Bar Planked:



Stile and Rail Construction Smooth Surface Planked

Pre-Routed Door Bottom Available in sizes:

 $3/0 \times 7/0$ 3/6 x 7/0



Primed Carrara Door with Stainless Steel Bent Strap Track and Mounting Board



*Carrara



**Primed 15 Lite

Carrara and Primed 15 lite:



Solid Core Smooth Surface Cove & Bead Sticking

*Available in sizes:

1/6 x 7/0 $2/6 \times 7/0$ 1/8 x 7/0 2/8 x 7/0 2/10 x 7/0 2/0 x 7/0 3/0 x 7/0 2/4 x 7/0

**Available size:

3/0 x 7/0

Interior Door Collection

Molded Doors



Avalon
3 Panel
Textured Surface
Cove & Bead Sticking



Caiman
2 Panel Arch Top
Smooth Surface
Cove & Bead Sticking
Solid Core Only



Camden
2 Panel Eyebrow Top
Textured Surface
Cove & Bead Sticking



Carrara
2 Panel
Smooth Surface
Cove & Bead Sticking
Solid Core Only



Cashal
2 Panel Planked Arch Top
Smooth Surface
Cove & Bead Sticking
Solid Core Only



*Colonist
6 Panel
Textured Surface
Cove & Bead Sticking



*Coventry
4 Panel
Smooth Surface
Cove & Bead Sticking



Craftsman III 3 Flat Panel Smooth Surface Craftsman Sticking



Impressions Mirror Side A - with surrounding Textured Surface Cove & Bead Sticking



*Madison 1 Flat Panel Smooth Surface Craftsman Sticking



*Monroe 2 Flat Panel Smooth Surface Craftsman Sticking



Princeton
2 Panel
Smooth Surface
Cove & Bead Sticking



*Rockport
5 Panel
Smooth Surface
Cove & Bead Sticking



*Smooth Colonist 6 Panel Smooth Surface Cove & Bead Sticking



Order Your Door Checklist Form

The following checklist will be useful in gathering complete quoting/ordering information
Customer Name: Job Name:
APPLICATION: Interior Exterior
<u>FRAMES</u>
Opening Size: W H 📮 Nominal 📮 Rough 📮 Existing
Wall Type: 🗖 New 📮 Existing 📮 Masonry 📮 Wood Stud 📮 Metal Stud
Finished Wall Thickness: Frame Depth 🖵 Overall 📮 Throat
Frame Type: 🗖 Masonry 🗖 Drywall 📮 Expandable 📮 EZ Flex 📮 EZ Fixed
Corner Construction: 🗖 Knocked Down 📮 Set-up/Welded Note: Drywall, EZ Fixed, EZ Flex and Expanable are KD only
Anchors: 🗖 Wire Masonry 📮 Wood Stud 📮 Metal Stud 📮 Existing Opening with expansion bolt or wood screws.
Gauge: Standard 16/18 Special - Specify (Punched and Dimpled)
Fire Rating: 🗖 B label (1-1/2 hour) 📮 C label (45 minute) 📮 (20 minute) 📮 (non-rated)
Finish: 🗖 Field Finish (by customer) 📮 Prefinished Color (Excludes Ez-Flex + EZ-Frame)
Steel Type: 🗖 Cold Rolled 📮 Galvanized 📮 Galvaneal 📮 Other - Specify
Handings: ☐ Single
Double INSWING OUTSWING INT EXT SEXT EXT EXT RA
DOORS
Type: HM Polystyrene Light Commercial MJ Steel Oak Birch Fiberglass
Design: ☐ Flush ☐ 2 Panel ☐ 6 Panel ☐ Metal Lite ☐ 10x10 ☐ 5x20 ☐ 3x33 ☐ 6x30 ☐ 22x28 ☐ 22x30 ☐ 24x20
Gauge: Standard 18/25 Special Specify Other:
Fire Label: \square B label (1-1/2 hour) \square C label (45 minute) \square (20 minute) \square (non-rated)
Opening: Single Door Pair of Doors
Astragal: 🔲 WITH Astragal 🔲 WITHOUT Astragal
Finish: Field Finish Prefinished Color
HARDWARE TO THE PROPERTY OF TH
Finish:
Hinges: Plain Bearing Plain NRP Ball Bearing Ball Bearing NRP Spring Door Closer: Heavy Traffic - 2701 Light Traffic - 1101
Exit Device: Rim Heavy Traffic - 2100 SVR Heavy Traffic - 2110 RIM Light Traffic - 1800 SVR Light Traffic - 1810
Panic Trim: Rose Passage Rose Classroom Escutsheon Classroom Other
Misc. Hardware: ADA Threshold Flush Bolts Perimeter Weatherstrip Viewer Adhesive Weatherstrip
□ Sweep □ Push Plate □ Pull Plate □ Kick Plate □ Wall Stop □ Dome Stop □ Kick Down Stop □ Split Astragal
Commercial Cylindrical Lock: Passage Privacy Entry Classroom Storage Single Cylinder Deadbolt
If I laurely come is to be a compulsed by others
Lock Brand: Lock Type: Cylindrical Deadbolt
Lock Function: Lock Number: Finish:


Special Order

MMI DOOR prides itself on the simple idea of "One Source, One Solution." If we don't stock it, we have a vast amount of resources at our disposal. The possibilities are endless when it comes to commercial doors and hardware. Below is a small sample of additional doors, frames and hardware we can provide:


DOORS

Besides our stock profiles, Hollow Metal and Wood Doors can be ordered in a variety of styles, as shown below. Special Order Hollow Metal can be ordered in 12, 14, 16 and 18 gauge, in cold rolled, galvanized Stainless Steel, Lead Lined, Sound Resistant and Bullet Resistant. Wood Doors can be ordered in any veneer of choice, Prefinished, Sound Resistant and Lead Lined.






EMBOSSED PANEL DESIGNS



FRAMES

Special order Hollow Metal frames can be ordered in 12, 14 and 16 gauge cold rolled or galvanized, Stainless Steel, Lead Lined, knocked down or welded. 3 sided, Sidelite, Transom or Borrowed Lites. Frames can be ordered to fit the wall conditions you require, from 3" to 14" thick.



FINISHED HARDWARE

Our complete line of hardware doesn't stop with what we stock, we have access to all major brands and types, including Concealed Hardware, Electric Hardware, Pivots, Auto-Operators, Alarm Devices and much more.

Glossary of Terms

At first glance, commercial doors and products can seem intimidating. Familiarizing yourself with the products, field applications and terminology can be a big help. Below are examples of some popular, everyday commercial products, their commercial door application and glossary to clarify common terms.

Our goal is to make commercial products easy to sell, source and service!

The leaf that opens first and the one to which the lock is Flush Bolt



Active Door




A door bolt, that when applied, is flush with the face or

	Active Door	applied.	Flush Bolt	edge of the door.
	Astragal (in a pair of doors)	A molding or strip whose purpose is to cover or close the gap between the edges of a pair of doors. Some types overlap, others meet at the center line of the gap.	Inactive Door (or Leaf)	That leaf of a pair of doors that does not contain a lock, is bolted when closed, and to which the strike is fastened to receive the latch or bolt of the active
	Ball Bearing Hinge	A hinge that is equipped with ball bearings between the hinge knuckles that reduces friction. Mainly used for heavy doors for ease of opening.	Kick Plate	door. A protective plate applied on the lower rail of the door to prevent the door from being marred.
	Continuous Hinge (also called Piano	A hinge designed to be the same length as the moving part to which it is applied, for example, the lid covering	Lock Set (or Latch)	A lockset, complete with trim, such as knobs, escutcheons or handles.
	Hinge)	the keyboard of a piano.	Mortise Lock	A lock which is mortised into the edge of a door which
	Coordinator	A device used on a pair of doors to ensure that the inactive leaf is permitted to close before the active leaf.	(Hall/Closet)	combines the two functions normally required on a door; latching and bolting.
		Necessary when an overlapping astragal is present and exit devices, automatic or self-latching bolts are used with closers on both door leaves.	Passage Function (Bed/Bath)	Knob or lever set most commonly used in hallways where a locking feature is not required.
•	Cylinder	The cylinder-shaped assembly (complete operating unit) containing the tumbler mechanism and the keyway (plug, shell, tumblers, springs and actuating device) into which the key is inserted to operate a lock and can only be actuated by the correct key.	Privacy Function	Knob or lever set most commonly used in bathroom or bedroom; can be locked from the inside with a push button emergency release feature.
			Push Plate	A plate applied to the lock stile to protect the door against soiling and wear.
	Door Hand	A term to describe the direction a door swings - Example RH - right hand or RHR - right hand reverse.	Pull Plate	A plate applied to the lock stile to grab and pull the door open and also protect the door against soiling and wear.
	Door Stop	A device to stop the swing or movement of a door at a certain point.	Spring Hinge	A hinge containing one or more springs to move the
D	Dust-Proof Strike	A strike with a spring plunger that completely fills the bolt hole when the bolt is not projected.		door into the desired position. It may be either single or double acting.
	Exit Device	A door-locking device designed to grant instant exit by pressing on a cross bar that releases the locking bolt and latch.	Threshold	A strip fastened to the floor beneath a door, usually required to cover the joint where two types of floor materials meet.



For more information on MMI DOOR products and services, please visit:

www.mmidoor.com



MMI DOOR LOCATIONS

Michigan (HQ)

6361 Sterling Drive North Sterling Heights, MI 48312 586.264.0950 800.686.9218 Fax: 586.264.5430

Ohio

400 Circle Freeway Drive Cincinnati, OH 45246 513.874.6771 800.215.3770 Fax: 513.870.0242

Pennsylvania

172 Plummer Road Sidman, PA 15955 814.487.7800 800.452.0251 Fax: 814.487.7850

